



## Drum Trailer 4701 / 4715

Flexible and easily operated drum trailer with tiltable drum holding frame, which is moved by the winch operating on the winch rope connected the holding frame and the chassis. The trailer incorporates facilities for a drum drive and the provision for drum braking allowing the unit to be used for recovery or for re drumming. The steel welded and hot dip galvanised chassis and lifting frame is equipped with full road suspension, overrun and parking brakes plus lights all in accordance with CE regulations. The trailer is prepared for a driving unit, which is used for reeling and reeling of cable and rope on a wooden drum. Further, the drum unit, which is equipped with a brake, which gives a balanced and controlled output. The trailer has 2 adjustable supportlegs at the rearside which stabilistate the usage of the machine.



Drive kit for the drum - compatible with Sahlins engine 2042 & 2060 - is available as an accessory.

Just like this duct boom (picture) that enables six smaller drums if needed.

### Technical data

<b><u>Model:</u></b>	<b><u>4701-0750</u></b>	<b><u>4701-1001</u></b>	<b><u>4715-1000</u></b>
Total weight:	750 kg	1300 kg	1800 kg
Trailer weight:	370 kg	370 kg	430 kg
Max load (with drum drive):	305 kg	855 kg	1295 kg
(without drum drive):	380 kg	930 kg	1370 kg
Drum size (drum drive suitable for K12—K24):	K9—K24	K9—K24	K9—K24
Tyers:	195/70R 14	195/70R 14	185 R14 C8
Dimensions:	L = 3 350 mm B = 2 160 mm H = 1 742 mm	L = 3 350 mm B = 2 160 mm H = 1 742 mm	L = 3 350 mm B = 2 160 mm H = 1 745 mm






## Engines

The trailer can be equipped with petrol- or hydraulic engine, with gear-box including forward and reverse gear. It is used together with the drive kit for reeling and unreeling of cable and rope on a wooden drum.

- P.No.: **2042-3000** (petrol engine, 5,5 hp)  
 P.No.: **2044-3000** (hydraulic engine)  
 P.No.: **2045-5000** (3 phase electric engine)  
 P.No.: **2060-1000** (petrol engine, 5,5 hp)



## Drive kit

The drivekit is used for reeling and unreeling of cable from wooden-drums in sizes K12-K24. The driving runs over 2 rubber /metalcovered wheels which can be adjusted laterally for best adapting on the drum.

- P.No.: **4701-0020** (Engine 2042 / 2044 / 2045)  
 P.No.: **4701-0030** (Engine 2060)



## Brake kit

The trailer has a gliding drumaxle with diam. 70mm and is delivered with distances for 105 and 130mm drumhole. The drumaxle is locked in it's workingposition with a specialconstructed lock without loose pins. The axle can even be equipped with drumbrake for a balanced and safe pulling from the cabledrum.

- P.No.: **4701-0010**



## Winter tyres

Qualitative and complete winter wheels to the trailer in the form of studded- alternatively friction tires.

- |          |                 |                     |
|----------|-----------------|---------------------|
| Studded  | <b>9581-028</b> | 215/75R16C 116/114R |
| Friction | <b>9581-029</b> | 215/75R16C 116/114R |



## Extension boom

Extension boom that enables handling of two drums. Maximum load on the upper drum is 120kg. This accessory is also compatible whit drum trailer 4720.

- P.nr.: **4720-0050**



## Duct boom

Exchangeable boom for six duct drums up to K10. Stop rings and cones are included.

- P.nr.: **4701-0080**